

RG-S5750-S





# Contents

1

Ruijie# write

Building configuration...

Write to boot config file: [/config.text]



# Contents

Ctrl Version: RGOS 10.4(3b16) Release(146430)  
MTD\_DRIVER-5-MTD\_NAND\_FOUND: 1 NAND chips(chip size : 134217728) detected  
1 nand chip(s) found on the target.  
Press Ctrl+C to enter Ctrl ...

// log 3s ctrl+c CTRL

Hot Commands:

-----  
-----

Ctrl>^C

Ctrl>^C

Ctrl>rename confi g. text confi g. bak

Ctrl>load //

Ruijie#copy flash: confi g. bak flash: confi g. text

Ruijie#copy



# Contents



[www.ruijie.com.cn](http://www.ruijie.com.cn)

RGOS

Ruijie#copy




Ruijie

www.ruijie.com.cn



# Contents



```
Ruijie#show tempr
```

```
Device-1:  
Current Tempr: 29.0 C
```

		指示灯灭	端口未 Link
1000M Link Up			绿色常亮
1000M 数据收发	1000Mbps RJ-45 接口指示	1-24	绿色闪烁
100/10M Link Up			黄灯常亮
100/10M 数据收发			黄灯闪烁

```
Ruijie#show fans
```

```
Device-1:
```

Item	Status	Serial Number	Ver	Speed
1	Normal	-	1	//normal
2	Normal	-	1	



CPU • i V i - Ü ä ½ Â K 3 ° ) T ¿ ! € \$ ñ † A ' 0 L



Ruijie#show interfaces counters

```
Interface : Gi gabi tEthernet 0/1
5 minutes input rate : 1034 bits/sec, 1 packets/sec
5 minutes output rate : 65 bits/sec, 0 packets/sec
InOctets          : 8918550
InUcastPkts      : 4
InMul ti castPkts : 103298
InBroadcastPkts  : 0
OutOctets         : 524352
OutUcastPkts     : 4
OutMul ti castPkts : 2298
OutBroadcastPkts : 0
Undersize packets : 0
Oversize packets : 0
collisions       : 0
Fragments        : 0
Jabbers          : 0
CRC alignment errors : 0
AlignmentErrors  : 0
FCSErrors        : 0
dropped packet events (due to lack of resources): 0
packets received of length (in octets):
```





# Contents















\_\_\_\_\_



\_\_\_\_\_



\_\_\_\_\_



\_\_\_\_\_

